



## OWNER MANUAL

### BR-72VW

#### Features:


- \*Car specific 2-way component speaker system
- \*7" woofer with paper-fibre cone and rubber surround
- \*Car specific high pass filter included
- \*28 mm / 1.1" silk dome tweeter
- \*Klippel® optimized
- \*Suitable for VW\*

\*VW is a registered trademark of Volkswagenwerk GmbH



\* May be incompatible with molds of some older model years. Please confirm whether it is compatible with your vehicle before purchasing.

BR-72VW	2-way Component System	
Impedance	4 Ohm	
Frequency response	70-20kHz	
Efficiency 1W/1M	90dB	
Power Handling(RMS)	60W	
Power Handling(max)	120W	
Crossover Frequency	3500 Hz(6/oct)	
Linear Parameters(TSP)	BR-72VW-MID	BR-72VW-TW
Membrane Material	Paper	Silk
Voice Coil Diameter	1"	1.1"
Resistance(Re)	3.6 Ohm	3.6 Ohm
Resonance Frequency(Fs)	70 Hz	1750 Hz
Mechanical Q factor(Qms)	4.97	
Electrical Q factor(Qes)	0.63	
Total Q factor(Qts)	0.56	
Equivalent air volume Vas	8.2L	
Mechanical mass(Mms)	11.3 g	





## OWNER MANUAL

### BR-72VW

#### Physical Dimensions:

