

FOR-X®

TX-58N USER MANUAL

TX-58N
High Efficiency Neodymium Tweeter
Ø 1 Inch Voice Coil 4Ω

FOR-X®

SPECIFICATIONS

| General Data | | Unit | |
|----------------------------------|-----------|--------|----|
| Overall Dimensions | 60*42.4 | mm | |
| Nominal Power Handling | 50 | W | |
| Transient Power 10ms | 100 | W | |
| Sensitivity | 102 | dB | |
| Frequency Response | 4.5K-20K | Hz | |
| Dome Material | Aluminum | | |
| Net Weight | 0.15 | kg | |
| Electrical Data | | | |
| Nominal Impedance | 4 | Ohm | |
| DC Resistance | 3.6 | Ohm | |
| Voice Coil and Magnet Parameters | | | |
| Voice Coil Diameter | 25.5 | mm | |
| Voice Coil Height | 1.8 | mm | |
| HE Magnetic Gap Height | 2.5 | mm | |
| Max. Linear Excursion | | mm | |
| Voice Coil bobbin | Kapton | | |
| Voice Coil Wire | CCAR | | |
| Number Of Layers | 1 | layers | |
| Magnet System Type | Neodymium | | |
| T-S Parameters | | | |
| Resonant Frequency | Fs | 4.5K | Hz |

FOR REFERENCE ONLY

