

X-12 PRO

12" Dual 4 ohm Subwoofer

FOR-X[®]

SPECIFICATIONS

General Data		Unit
Overall Dimensions	322mmx172mm	mm
Nominal Power Handling	1200	W
Maximum Power	3600	W
Sensitivity	90	db
Frequency Response	20-250	Hz
Cone Material	Paper Cone	
Basket	Aluminum	
Net Weight	9.0	kg
Electrical Data		
Nominal Impedance	4+4	ohm
DC Resistance	3.6+3.6	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	76.5	mm
Voice Coil Height	38	mm
HE magnetic Gap Height	10	mm
Voice Coil bobbin	ASV	
Number of Layers	4L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	0.07	Cms
Mechanical Q Factor	3.82	Qms
Electrical Q Factor	0.66	Qes
Total Q Factor	0.57	Qts
Moving Mass	293	Mms
Eq.Cas AIR Load	23.5	Vas
Resonant Frequency	36	Fs
Effective Piston Area	530 cm ²	SD

FEATURES

- * Aluminum Basket
- * 120 Oz High Flux Ferrite Magnet System
- * 3" Voice Coil
- * 3600 Watts Peak Power Handling

Dimensions

